


## Embeddable, Single-Channel Link 16 Comms for SWaP-Constrained Systems



With Viasat's Battlefield Awareness and Targeting System-Embedded 1500 (BATS-E 1500) Size, Weight and Power (SWaP)-constrained systems, including targeting pods and network enabled weapons, are now accounted for in the Common Operational Picture. This 360-degree visibility provides all Link 16 network participants with the ability to see, relay and share situational awareness data and allows for more accurate tracking, identification and engagement so controllers now have a clear view of the battlespace.

Designed for missions with longer transmission ranges, the low SWaP BATS-E 1500 is optimized for embedded applications. Controllers now have the ability to send target updates while in flight for secure, reliable weapons delivery, so as to significantly decrease the time in high-threat environments.

The BATS-E 1500's Enhanced Throughput (ET) mode boosts Link 16's protected data rate of 115 Kbps to over 1.1 Mbps. When combined with the Concurrent Multiple Reception (CMR) capability, the BATS-E 1500 is the first Link 16 radio capable of data rates in excess of 2 Mbps. The Concurrent Multinet (CMN) and Concurrent Contention Receive (CCR) features have also been implemented in the latest version of the BATS-E 1500. With Link 16 Cryptographic Modernization, the BATS-E also implements the latest high assurance algorithms using a field proven programmable crypto engine to securely serve joint and coalition mission requirements, while maintaining backwards compatibility with legacy communications systems.

For platforms that have traditionally lacked Link 16 network access, the Viasat BATS-E 1500 provides a cost-effective option for integrating Link 16 into existing targeting and weapon systems without the need for major platform modifications. This approach ensures that integration costs are kept to a minimum, while providing full interoperability with other platforms that are already outfitted with Link 16 communications.

The Viasat BATS-E 1500 combines full Link 16 functionality in a compact, embeddable form factor, delivering real-time accurate targeting data to help controllers make split-second decisions to execute more missions with precision.

### BATS-E 1500 AT-A-GLANCE

#### Mission Flexibility

- » Single-channel Link 16 terminal
- » Embeddable form factor
- » Low, size, weight, and power
- » Jam resistant for operations in contested and denied access environments

#### Command and Control

- » Status/weapons load/time on station
- » Sensor information sharing
- » WILCO/CANTCO

#### Target Attack

- » Target update
- » Mobile target attack
- » Ideal for SWaP-constrained platforms
- » Targeting pods
- » Network enabled weapons

# Viasat BATS-E 1500

## SPECIFICATIONS AND TECHNICAL FEATURES

### PERFORMANCE

- » Frequency Range 969 to 1206 MHz Link 16
- » Transmission Modes Link 16 TDMA, all OP modes and enhanced throughput
- » Antenna Port
  - Link 16 50 Ω
- » Data Interfaces Ethernet/USB, Full Platform-J interface
- » Dimensions (W x H x D) 5.5 x 4.25 x 5.25 in.; 13.9 x 10.8 x 13.3 cm
- » Volume 123 cu in. (2,015.61 cc)
- » Weight 6 lb

### TRANSMITTER

- » Power Output 63 W and 8 W (air-to-air transmission ranges in excess of 200 nm)

### WAVEFORMS

- » L-band Link 16 data including enhanced throughput modes

### ENVIRONMENTAL

- » Operating Temperature -45° to +74° C; -49° to +165.2° F
- » Storage Temperature -33° to +71° C; -27.4° to +159.8° F

### POWER CONSUMPTION


- » Average DC Power Consumption @ 63W RF output power: 50W @ 28VDC
- » Average DC Power Consumption @ 8W RF output power: 42W @ 28VDC

### FEATURES

- » Embeddable, single-channel, single antenna Link 16
- » Modular design for easy growth
- » Fully conduction cooled
- » Link 16 data
- » Link 16 Frequency Remapping (FR)
- » Enhanced Throughput (ET)
- » Concurrent Multi-Net (CMN)
- » Concurrent Contention Receive (CCR)
- » Interoperable with: JTIDS, MIDS-LVT, MIDS JTRS, STT, BATS-D AN/PRC-161, and all fielded Link 16 terminals
- » Cryptographic Modernization Initiative compliant

### GROWTH CAPABILITIES

- » Enhanced anti-jam
- » Link 16 precision navigation



## CONTACT

6155 El Camino Real, Carlsbad, CA 92009-1699, USA

U.S. SALES  
TEL 760 795 6334  
EMAIL [bats@viasat.com](mailto:bats@viasat.com)

INTERNATIONAL SALES  
TEL +1 760 476 2675  
EMAIL [bats.international@viasat.com](mailto:bats.international@viasat.com)

TECHNICAL SUPPORT  
TEL 866 496 1584  
EMAIL [tdl-techsupport@viasat.com](mailto:tdl-techsupport@viasat.com)

EMAIL [bats@viasat.com](mailto:bats@viasat.com)  
WEB [www.viasat.com/link-16](http://www.viasat.com/link-16)



PRELIMINARY