

### TRANSPORTABLE, READY-TO-USE



The Viasat Small Tactical Terminal (STT) Ruggedized Mobile System is a small, 4U transportable case unit offering a convenient way to operate your Link 16 system. Outfitted with all of the equipment you need for dual-channel operation, this mobile system can be used in any number of venues including operational, training, demonstrations, and testing.

The mobile system features two (one for each channel) Viasat Multi-Platform Integrated Controllers (MIC), a rugged control unit that offers both local and remote operation through an easy-to-operate web interface:

- » Channel Power
- » Crypto Hold
- » LTTI
- » IFF Emergency
- » KDU Access Connector
- » Crypto Zeroize
- » Crypto Loading/Management
- » Preset Selection Interface
- » BIT Status
- » Important STT Status (battery, versions, cipher switch, etc.)
- » ASCII Console
- » USB Interface (loading mission plans, files, software all from a web browser)

The MIC offers a standard fill connector interface to the STT for ease of loading crypto with standard fill devices.

The mobile system also includes the Viasat Multi-Platform Audio Component (MAC), a rugged interface unit that provides independent or simultaneous dual-channel voice (receive and transmit). It features a custom built 30 W quad-speaker system that has been tuned to enhance audio quality. The MAC is compatible with most headsets and handsets and is also controlled through the same, intuitive web interface that is provided by the MIC.

### MOBILE SYSTEM AT-A-GLANCE

#### Features

- » Multi-Platform Integrated Controller (MIC)
- » Multi-Platform Audio Component (MAC)
- » Power and I/O panel for input power to the mobile system as well as standard interfaces to the STT:
  - CH1/CH2 MIDS Support Port/Ethernet (RJ45)
  - CH1 & CH2 DTE (DB15)
  - Link 16 1PPS ETR Input – 10v, 50ohm (BNC)
  - Link 16 Antenna A & B (NTYPE)
  - CH1 & CH2 UHF/VHF RF (TNC)
  - CH1 & CH2 MIC Web Interface (RJ45)
  - GPS 1PPS Output (BNC)
  - GPS USB Serial Console (USB-B)
- » Internal rack GPS to provide Link 16 1PPS ETR strobe and access to NMEA streams for an external host system via a USB serial connection

#### Ordering Information

PN: 1265287      STT Ruggedized Mobile Rack

## SPECIFICATIONS AND TECHNICAL FEATURES

### PERFORMANCE

<b>Input Power</b>	120 VAC 60 Hz, 20 amp (IEC C20) 230/240 VAC 50 Hz, 10 amp (IEC C14)
<b>Dimensions</b>	11.1 x 22.5 x 34.5 in.
<b>Weight (Approximate)</b>	130 lbs

### STANDARD CABLES

» <b>W1, W2, &amp; W3</b>	Voice/Data/Control
» <b>W4 &amp; W10</b>	Crypto/Voice
» <b>W5</b>	DC Power Cable
» <b>W6 &amp; W7</b>	UHF/VHF
» <b>W8 &amp; W9</b>	Link 16 RF Cables

### STANDARD ACCESSORIES

- » Input Power Cables
  - 120 VAC NEMA 5-20P to IEC C19
  - 230/240 VAC AS/NZ4417 to IEC C13
  - 230/240 VAC CEE 7/7 EURO SCHUKO to IEC C13
  - (please specify if other international cables are required)
- » BNC to BNC 1PPS Jumper Cable
- » H-250 Handset
- » 2x KDU
- » 4x Ethernet Cables
- » 4x 50W RF Attenuators
- » 2x DB15 to DB15 Cables
- » USB-A to USB-B Cable
- » User Guide



## CONTACT

6155 El Camino Real, Carlsbad, CA 92009-1699, USA

U.S. SALES

TEL 760 795 6334

EMAIL [mids.us@viasat.com](mailto:mids.us@viasat.com)

INTERNATIONAL SALES

TEL +1 760 476 2675

EMAIL [mids.international@viasat.com](mailto:mids.international@viasat.com)

TECHNICAL SUPPORT

TEL 866 496 1584

EMAIL [tdl-techsupport@viasat.com](mailto:tdl-techsupport@viasat.com)

EMAIL [mids@viasat.com](mailto:mids@viasat.com)

WEB [www.viasat.com/link-16](http://www.viasat.com/link-16)

