



The SurfBeam 2 Pro Portable Terminal delivers affordable high-speed Internet access via satellite for workers at temporary sites. The rugged, lightweight terminal is based on ViaSat SurfBeam® 2 technology and builds on the success that made ViaSat SurfBeam the product of choice for WildBlue, the world leader in Ka-band direct-to-home Internet service. With nearly a million terminals delivered around the globe, the SurfBeam network has a record of proven reliability, scalability and performance.

HIGH-PERFORMANCE, COST-EFFECTIVE INTERNET ACCESS ON THE GO

The ViaSat SurfBeam 2 Pro Portable Terminal is designed for users requiring high throughput connectivity in a compact and portable package. Field reporters, remote medical and peace workers, and emergency responders benefit from DSL-like Internet speeds with the convenience of “near-instant” connectivity even in locations where no other communications infrastructure is available. The form factor is ruggedized to support operation in harsh conditions and supports multiple configuration options to suit user needs. The complete terminal, including the satellite terminal and antenna, can be packed into a single case for transit and is lightweight enough to be carried by a single user.

The unit enables fast web browsing and supports video streaming, file transfers, VPN connections, and bandwidth-intensive Internet applications. It is capable of delivering downstream rates up to 50 Mbps and upstream rates up to 20 Mbps, and provisioning tools enable the network operator to create different classes of service with configurable downstream and upstream rates. The modem has an embedded acceleration client that works with acceleration servers in the gateway to provide a faster, more responsive user experience. With four standard Ethernet connections, the terminal natively supports up to 4 IP devices, such as PCs, cameras, and routers as well as other user equipment. The antenna is available in 2 sizes (75cm and 50cm) and includes a collapsible satellite reflector and feed, transmit and receive electronics, and can be deployed with the modem or in a standalone configuration.

EASY INSTALLATION AND OPERATION

The compact SurfBeam 2 Pro Portable Terminal is designed for a quick and reliable user installation in less than 10 minutes by personnel with minimal satellite training. It is part of a complete SurfBeam 2 system that also includes an innovative Satellite Modem Termination System (SMTS) gateway and Network Management Systems (NMS) that facilitate subscriber management with features such as automated service provisioning, diagnostics, and customer support.

TERMINAL AT-A-GLANCE

- » Easily portable high-speed connectivity
- » Ruggedized for operation in harsh environments
- » Utilizes affordable, high-capacity Ka-band satellite bandwidth
- » Supports high-speed live video uplinks
- » Quick set-up using built-in antenna pointing aid for rapid satellite acquisition
- » Integrated 4-port IP router
- » Web GUI local management and SNMP-based remote management and control

APPLICATIONS

- » Always On — rapid Internet access
- » Satellite news gathering
- » Disaster relief support
- » Emergency medical response reporting



SurfBeam 2 Pro Portable Terminal Specifications

FORWARD CHANNEL

Modulation/Coding

- » 16-APSK Rate 2/3, 3/4, 4/5, 5/6, 8/9
- » 8-PSK Rate 3/5, 2/3, 3/4, 5/6
- » QPSK Rate 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6
- » Adaptive Coding & Modulation

Symbol Rate 10 - 52 Msps

RETURN CHANNEL

Modulation/Coding

- » 8-PSK Rate 7/12, 2/3, 3/4
- » QPSK Rate 3/8, 1/2, 5/8, 3/4
- » BPSK Rate 1/2
- » Automatic power control and rate adaptation

Symbol Rate 625, 1250, 2500, 5000, 10000 and 20000 Ksps

ANTENNA

Input Frequency 18.3 - 20.2 GHz

Output Frequency 28.1 - 30.0 GHz

Polarization Circular, with remote switching option

Mounting As part of terminal or deployed independently

Cable Length (max) 50 m

75 CM REFLECTOR

- » **Nominal EIRP** 48.7 dBW
- » **Nominal G/T** 17.5 dB/K

50 CM REFLECTOR

- » **Nominal EIRP** 45.2 dBW
- » **Nominal G/T** 14.0 dB/K

ENVIRONMENTAL

Operational -10° to +50° C (antenna -40° to +65° C)

Storage -35° to +65° C

Altitude 3000 m

Wind 45 km/h

Shock and Vibration Per ISTA, July 2000, Procedure 1A

Ingress Protection IP 66

POWER

AC AC Power Supply 100-240 VAC; 50-60 Hz

DC 12-32 VDC

Battery Supports a variety of battery options

Power Consumption 80W / Typical Usage

PACKAGING AND WEIGHT

Packaging Options & Dimensions

- » 1 case with linear size less than 158 cm / 62 in (airline checkable)
- » 2 cases each with size less than 115 cm / 45 in (airline carry-on)
- » **Terminal Weight** Approximately 20 lbs (9 kgs)

INTERFACES

Ethernet 4x10/100 BaseT, RJ-45

Power Input 2xD38999

Power Output 1xD38999

Antenna F Connector (male)

NETWORKING

IP Internetworking

- » Integrated 4-port IP router
- » Transparent TCP and HTTP acceleration
- » Packet classification and filtering

POINTING

- » On-board pointing information display
- » Integrated signal strength indicator

MANAGEMENT

Modem Web GUI local management and SurfBeam 2 network SNMP-based remote management and control

Router Web GUI local management

Display Pointing and status indication

LEDs Quick terminal status



CONTACT

COMMERCIAL SALES vsatsales@viasat.com

GOVERNMENT SALES gov.satcom@viasat.com

UK SALES sales@viasat.uk.com

ATLANTA 1725 Breckinridge Plaza, Duluth, GA 30096
TEL +1.678.924.2400 FAX +1.678.924.2480

NEW DELHI 601 New Delhi 611-A, JMD Pacific Square
Sector 15, Part 2, NH #8 Gurgaon 122001 Haryana, India
TEL +91.124.402.5200 FAX +91.124.402.5252

ROME Piazza del Popolo 18, 00187 Rome, Italy
TEL +39.0636712432 FAX +39.0636712400

SAN DIEGO 6155 El Camino Real
Carlsbad, CA 92009
TEL +1.760.476.2200 FAX +1.760.929.3941

SYDNEY Unit 4/22 Narabang Way
Belrose, NSW 2085, Australia
TEL +61.2.9986.3888 FAX +61.2.9986.3899

UNITED KINGDOM Sandford Lane, Wareham, Dorset, BH 20 4DY
TEL +44 (0) 1929 55 44 00 FAX +44 (0) 1929 55 25 25